

- Infrared and 433MHz RF control
- Fully customizable graphical interface
- 2.4" Color LCD touchscreen display
- Tilt-activated backlit buttons
- Convenient, intuitive selection of buttons
- All hard buttons are fully programmable



Pro24.r Remote shown on the Pro24.Dock Charging Dock

Elevate the media room... and more.

The Pro24.r is a purpose-built, hard-button remote for professional AV. Large, labeled buttons are easy to find, even across the room.

Use it alone for simple, line-of-sight IR control, or pair with the ProLink.r processor for full multi-source systems. Once programmed, the system is locked in — no cloud, no surprise updates, no end-user tinkering.

The included Pro24.Dock charging dock, in matching gloss black, ensures that the remote is always charged and ready.

Rock solid reliability.

When paired with the ProLink.r control processor, the Pro24.r remote delivers fast and reliable 433 MHz one-way RF communication.

The ProLink.r processor features an Ethernet port for network control of devices, four IR ports, two voltage-sensing inputs, and one-way (LAN) support for the ProPanel App on Apple iPad® and iPhone®.



ProLink.r Control Processor (sold separately)

SPECIFICATIONS

Color touchscreen display	2.4" TFT LCD
RF control	1-way (433 MHz)
Compatible control processor	Pro Control ProLink.r
Control via infrared (IR)	Yes (Capable of IR learning)
Charging	Pro24.Dock (Included) or USB Cable
Rechargeable battery	Lithium Ion
Charging dock (included)	Micro USB B input plug, 5.0V @ 1.0A
Number of commands and macros allowed	Unlimited (Determined by available memory)
Number of controlled devices	Unlimited (Determined by available memory)
Customizable graphics via programming software	Yes, Pro Control Studio
Dimensions H x W x D (remote only)	9.79" x 2.23" x .9" (248.6mm x 56.6mm x 22.9mm)
Warranty	3 years (parts & labor)